

US009606692B2

# (12) United States Patent

## Chang et al.

(10) Patent No.: US 9,606,692 B2

(45) **Date of Patent:** Mar. 28, 2017

#### (54) CONTROLLER FOR POSITION DETECTION

(71) Applicant: EGALAX\_EMPIA TECHNOLOGY

INC., Taipei (TW)

(72) Inventors: Chin-Fu Chang, Taipei (TW);

Cheng-Han Lee, Taipei (TW); Chi-Hao Tang, Taipei (TW); Shun-Lung Ho, Taipei (TW)

(73) Assignee: EGALAX\_EMPIA TECHNOLOGY

INC., Taipei (TW)

(\*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 15/015,715

(22) Filed: Feb. 4, 2016

(65) Prior Publication Data

US 2016/0170534 A1 Jun. 16, 2016

## Related U.S. Application Data

- (63) Continuation of application No. 14/607,809, filed on Jan. 28, 2015, now Pat. No. 9,285,940, which is a continuation of application No. 14/033,872, filed on Sep. 23, 2013, now Pat. No. 8,970,552, which is a continuation of application No. 12/923,808, filed on Oct. 8, 2010, now Pat. No. 8,570,289.
- (60) Provisional application No. 61/298,252, filed on Jan. 26, 2010, provisional application No. 61/298,243, filed on Jan. 26, 2010, provisional application No. 61/250,051, filed on Oct. 9, 2009.
- (51) Int. Cl. G06F 3/041 (2006.01) G06F 3/044 (2006.01) G01R 27/26 (2006.01) G06F 3/047 (2006.01)

#### (52) U.S. Cl.

(58) Field of Classification Search

## (56) References Cited

#### U.S. PATENT DOCUMENTS

4,639,720 A	1/1987	Rympalski et al	
5,374,787 A	12/1994	Miller et al.	
5,412,200 A	5/1995	Rhoads	
5,543,588 A	8/1996	Bisset et al.	
5,644,512 A	7/1997	Chernoff et al.	
	(Continued)		

#### FOREIGN PATENT DOCUMENTS

CN	1164286	11/1997
CN	1596412	3/2005
	(Continued)	

Primary Examiner — Ricardo L Osorio (74) Attorney, Agent, or Firm — WPAT, PC; Justin King

### (57) ABSTRACT

A controller for position detection is disclosed. At least one first 1-D position corresponding to at least one external object is determined based on signals of a plurality of first sensors by self-capacitance detection. Then, at least one second 1-D position corresponding to the at least one first 1-D position is determined based on signals of a plurality of second sensors by mutual-capacitance detection.

## 12 Claims, 21 Drawing Sheets

